

Tubing Size 1/2" - 3/4"
1/2" Flow Glass Filled Polypropylene

65GP Series Socket

65GP Series couplings offer 1/2" flow capacity and are manufactured from a high performance glass filled polypropylene. 65GP couplings have a full flow, non-valved, smooth internal bore that allows for maximum flow with minimal turbulence. 65GP couplings are extremely durable and are well suited for applications that require chemical resistance. 65GP Series couplings interconnect with and are compatible with many other plastic latch type couplings.



Features:

- Audible "click" when connected
- Connects with other plastic latch type couplings
- Extremely durable
- Integral end terminations
- Small and compact
- One hand operation
- Resistant to acids and chemicals
- Latch guard eliminates accidental disconnects
- Stainless steel latch spring
- Large push button

Performance Ratings:

- Operating Pressure: Vacuum to 120psi; (8.3bar)
- Temperature: -40°F to 180°F; (-40C to 82C)
- Flow Capacity: 1/2" Size

Materials & Construction:

- Bodies & Terminations: Glass Filled Polypropylene
- Thumb-latch: Acetal copolymer
- Springs: Stainless Steel
- O-rings: EPDM (others available)



| IN-LINE SOCKET | | | | | |
|----------------|-----------|--------|-------|--------|--|
| Non-Valved | Tube Size | Length | Width | Height | |
| 65GP-S2-12 | 3/4" H.B. | 2.93" | 1.37" | 1.45" | |



Tubing Size 1/2" - 3/4"
1/2" Flow Glass Filled Polypropylene

65GP Series Plug



| MALE THREAD PLUG | | | | | |
|------------------|-------------|--------|-------|--------|--|
| Non-Valved | Thread Size | Length | Width | Height | |
| 65GP-PF1-08 | 1/2" NPT | 1.95" | 1.00" | 1.00" | |



| IN-LINE PLUG | | | | | |
|--------------|-----------|--------|-------|--------|--|
| Non-Valved | Tube Size | Length | Width | Height | |
| 65GP-PF2-08 | 1/2" H.B. | 1.95" | 1.00" | 1.00" | |

