

New Value Connectors for Simple Vacuum, Leak and Pressure Testing Applications - Simple to Use, Adjust, and Maintain!

The *EZ Series Seal* manual connectors for reduced pressure is the latest innovation for testing:

- Radiators, Hoses, Reservoirs
- Fuel Tanks, Pumps, Filters
- Engines, Axles, Transmissions
- Plastic Molded Components
- Castings, Fabricated Housings
- Small Appliances, Pumps
- Plumbing Fixtures
- Hydronic Heating
- Tubing and Assemblies



- Simple adjustment - Twist to adjust collar is easily sized for various seal diameters
- Quick change seal sets to accommodate multiple size tubing and port applications
- Simple design and field service maintenance kits require no special tools for easy seal replacement
- High flow design can be quickly adapted for plug style applications
- 2 way actuation handle is simple and ergonomic for production applications
- Mix and match seal sets can be used to seal tapered or unique testing applications
- See your local FasTest distributor for more information and support

[Watch Product Demo Link](#)

FasTest - The One Stop Shop for Testing!

The FasTest EZ Series Seal connectors are the ideal solution for low pressure, manual applications and a compliment to the highly engineered FasTest automated connector products.

Common Applications:



Molded Plastic Components



Shell and Tube Heat Exchangers



Evaporator Cores

Specifications:

Pressure rating. Vacuum to 50 psi / 3.44 bar (clean and dry surface pneumatic applications)
 Materials Aluminum housing with Stainless Steel components, Molded Delrin handle
 Seals Neoprene (main), Buna N (internal)

Body Size	Part Number	Sealing Range	Insertion Depth	Termination Port	Flow Diameter	Maintenance Kit
1	ZN1-01	0.375"-0.394"	0.57"	1/8" NPT	0.10"	ZNB1-0360 ZNB1-11 ZNB1-12 ZNB1-13
	ZN1-11	0.394"-0.472"				
	ZN1-12	0.472"-0.551"				
	ZN1-13	0.551"-0.630"				
2	ZN2-21	0.630"-0.709"	0.77"	1/4" NPT	0.17"	ZNB2-21 ZNB2-22 ZNB2-23
	ZN2-22	0.709"-0.787"				
	ZN2-23	0.787"-0.866"				
3	ZN3-31	0.866"-0.945"	1.20"	1/4" NPT	0.26"	ZNB3-31 ZNB3-32 ZNB3-33
	ZN3-32	0.945"-1.024"				
	ZN3-33	1.024"-1.102"				
4	ZN4-41	1.102"-1.181"	1.25"	3/8" NPT	0.28"	ZNB4-41 ZNB4-42 ZNB4-43
	ZN4-42	1.181"-1.260"				
	ZN4-43	1.260"-1.339"				

- **Additional value - 5 complete rebuilds to extend connector service life in each maintenance kit!**
- **See your local FasTest distributor for more information and support**

Product Safety:

All FasTest products have been designed with safety in mind, however, it is the responsibility of the product users to design each process in such a way to avoid mishaps that can cause physical hazard or property loss. Secondary restraints such as safety chains, shields, cages or fixtures are all good choices depending on the application. FasTest can recommend or assist you in clarifying potential hazards of your application.